


Rotule SI
GIR30-UK-DURBAL - GIR30-UK-DURBAL
<https://www.123roulement.com/roulement-palier/rotule/si/gir30-uk-durbal>

GIR30-UK

female thread:
maintenance free,
according to
DIN ISO 12240-4;
series E



Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...UK (UK-2RS) pressed into rod end body. Sliding combination steel / bronze-PTFE composite. Bore diameter d ≥ size 35 with additional seal on both sides (e.g. DGR... UK-2RS) bore diameter d ≥ size 17 additional seal on both sides upon request.



Rod end body:
surface zinc plated

Sliding combination:
steel / bronze-PTFE fabric

Inner ring:
bearing steel, hardened, ground and spherical surface chromium plated

Outer ring:
steel body pressed around, outer race lined with bronze-PTFE composite

Lubrication:
no lubrication necessary, maintenance free

order number		measurement [mm]						
right hand thread	left hand thread	d	G	B	C ₁	d ₂	d ₄	
GIR 30 UK		30	M 30 x 2	22	19,0	73	40,0 50	

type	measurement [mm]			α [°]	load rating C ₀ [kN]	weight [kg]
	l ₃ min	h	W			
GIR / GIR 30 UK	56	110	41	6	110,0	0,930

CARACTÉRISTIQUES PRODUIT

Marque	DURBAL
N° Ean13	3663952494005
Diam. intérieur	30 mm
Diam. intérieur	1.181" inch
Diam. extérieur	73 mm
Diam. extérieur	2.874" inch
Epaisseur	22 mm
Epaisseur	0.866" inch
Type	SI
Poids	930 g
Filetage	Filetage à droite
Lubrification	sans
Conditionnement	1
Norme	Sans norme

contact@123roulement.com
03 59 36 04 90
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE