

## Roulement à aiguilles NA6901-JTEKT - NA6901-JTEKT

<https://www.123roulement.com/roulement-palier/roulement-aiguilles/aiguilles/na6901-jtekt>

**Machined ring needle roller bearings** **Koyo**

*F<sub>W</sub> 29 – 37 mm*  
With inner ring

NA69

| F <sub>w</sub>                  | d  | D                      | B  | B <sub>1</sub><br>min. | r <sub>min</sub> | Boundary dimensions (mm) |                | Basic load ratings (kN) |                    | Limiting speeds <sup>1)</sup> (min <sup>-1</sup> ) |   | Bearing No. |
|---------------------------------|----|------------------------|----|------------------------|------------------|--------------------------|----------------|-------------------------|--------------------|--|---|-------------|
|                                 |    |                        |    |                        |                  | C <sub>r</sub>           | C <sub>0</sub> | Without oil lub.        | Without inner ring |  |   |             |
| 16                              | 12 | 24                     | 22 | —                      | 0.3              | 16.3                     | 21.7           | 27 000                  | —                  | —  | — | —           |
| <b>Mounting dimensions (mm)</b> |    |                        |    |                        |                  |                          |                |                         |                    |  |   |             |
| With inner ring                 |    | d <sub>s</sub><br>min. |    | D <sub>s</sub><br>max. |                  | r <sub>s</sub><br>max.   |                | (Refer.) Mass (kg)      |                    | (Refer.) Applicable inner ring No.                 |   |             |
| NA6901                          |    | 14                     |    | 22                     |                  | 0.3                      |                | 0.030                   |                    | 0.045  |   | IRMT121622  |

[Note] 1) Limiting speeds of bearing number NA69...UU indicates the value of sealed and grease lubricated bearings.  
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

## CARACTÉRISTIQUES PRODUIT

|                 |               |
|-----------------|---------------|
| Marque          | JTEKT         |
| N° Ean13        | 3663952477848 |
| Diam. intérieur | 12 mm         |
| Diam. intérieur | 0.472" inch   |
| Diam. extérieur | 24 mm         |
| Diam. extérieur | 0.945" inch   |
| Epaisseur       | 22 mm         |
| Epaisseur       | 0.866" inch   |
| Poids           | 45 g          |
| Conditionnement | 1             |

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE